

## 36 CELL POLYCRYSTAL DATASHEET

# LEXRON

FOR A LIVEABLE WORLD



### POSITIVE TOLERANCE

Guaranteed 0- +5W positive power output tolerance ensures high reliability



### SELF CLEANING

Anti-reflective, hydrophobic coating improves light absorption and reduces surface dust



### STRONG AIR RESISTANCE

Entire module certified to withstand high wind loads (2400 Pascal) and snow loads (5400 Pascal)\*



### HIGH PERFORMANCE

Excellent performance under low light environments (mornings, evenings and cloudy days)



PEAK POWER	OPEN CIRCUIT VOLTAGE Voc (V)	SHORT CIRCUIT CURRENT Isc (A)	PEAK POWER Vmp (V)	PEAK CURRENT Imp (A)	SIZE (mm)	CELL NUMBER (pcs)	NET WEIGHT (kg)
10W	22,32	0,67	18,60	0,56	300 x 300 x 20	36	1,3
22W	22,32	1,38	18,60	1,22	362 x 433 x 20	36	1,68
42W	22,32	2,58	18,60	2,33	679 x 433 x 20	36	3,8
65W	22,32	3,69	18,60	3,49	598 x 679 x 20	36	5,4
85W	22,32	4,82	18,60	4,57	791 x 679 x 25	36	7,0
105W	22,32	5,95	18,60	5,65	983 x 679 x 25	36	8,5
125W	22,32	7,09	18,60	6,72	1148 x 679 x 25	36	9,5
170W	22,32	9,64	18,60	9,14	1505 x 679 x 30	36	11,9